PROJA+ file copy AA

NSWC TR 81-149

FISH-KILL RANGES FOR OIL WELL SEVERANCE EXPLOSIONS

BY JOHN F. GOERTNER
RESEARCH AND TECHNOLOGY DEPARTMENT

1 APRIL 1981

Approved for public release, distribution unlimited.



NAVAL SURFACE WEAPONS CENTER

Dahlgren, Virginia 22448 • Silver Spring, Maryland 20910



FOREWORD

This report applies the dynamical model for explosion injury to fish developed in NSWC/WOL TR 76-155 to the problem of predicting fish-kill from an oil well severance explosion. This study was funded by the U.S. Geological Survey, which has been assigned the task of regulating off-shore drilling operations -- including the removal of abandoned wellheads.

The author thanks his colleagues David O'Keeffe for help with the kill probability computations and Robert Thrun for assistance in using his computer program to make the kill probability contour plots.

J. F. PROCTOR By direction

										•
·								•		8
					•					
					•					
							•			
			•							
							•		•	
			* **						•	
					•					
	and the second							•		
							•			
				•						
					•					
		•								
	· · · · · · · · · · · · · · · · · · ·							-	• • • • • •	
, .										
			•				•			
•										
						•				
				•		•				
					•			•		
		•								
·								٠		
	•									
			•	•						

	Y CLASSIFICATION OF THIS PAGE (When	Date Entered				
			 -			
i						
:						
	•. •					
						•
	•		٠.		•	
ř						
	A contract of the second second					
						٠
					•	
						•
			1			
			•			
	· .					
	•					
			·			

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT COCUMENTATION	PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	
NSWC TR 81-149		
4. TITLE (and Subtitle)		5. TYPE OF REPORT & PERIOD COVERED
FISH-KILL RANGES FOR OIL WELL SEV	/ERANCE	Final Report
EXPLOSIONS	•	5. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s)	-	8. CONTRACT OR GRANT NUMBER(*) U.S. Geological Survey
John F. Goertner		Annron. No. 1490804
33		Author. Ng-6102-05813(64)
9. PERFORMING ORGANIZATION NAME AND ADDRESS		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
Naval Surface Weapons Center White Oak, Silver Spring, Maryla	nd 20910	<u> </u>
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE 1 April 1981
U.S. Geological Survey		13. NUMBER OF PAGES
Reston, VA 22092		36
14. MONITORING AGENCY NAME & ADDRESS(If differen	nt from Controlling Office)	15. SECURITY CLASS, (of this report)
•		UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)	`	
Approved for public release, dis		
17. DISTRIBUTION STATEMENT (of the abetract entered	in Block 20, if different fro	om Report)
	•	
18 SUDDI EMENTARY NOTES		
18. SUPPLEMENTARY NOTES		
1		
19. KEY WORDS (Continue on reverse side if necessary s		
Fish-Kill Lethal Ranges	Oil Well Severar Wellhead Removal	
Swimbladder Fish	Shock Waves	-
Underwater Explosions		•
Underbottom Explosions 20. ABSTRACT (Continue on reverse side if necessary a	nd identify by block number	, , , , , , , , , , , , , , , , , , , ,
Computations based on the extrem	me values of commu	pression and extension of the
fishes' swim bladderin response estimate lethal ranges from wel	lhead severance e	explosions. The computations
were done using an equivalent-we	eight bare charge	e in free water which was
matched to measured data show pulse from a 1/2-scale wellho	ckwave p e ak pres:	sure, decay constant and im-
contour plots of 10%, 50% and 90	0% kill probabil	ity for 1-oz, 1-10 and 30-10
swimbladder fish in water 200,	500 and 1000 fee	t deep.

CONTENTS

Chapter		Page
1	INTRODUCTION	1-1
2	CALCULATION INPUTS	2-1
	PRESSURE-TIME INPUT	2-1
	EQUIVALENT FREE-WATER EXPLOSION	2-7
3	KILL PROBABILITY CONTOURS	3-1
4	CONCLUSIONS	4-1
5	DISCUSSION	5-1
	ILLUSTRATIONS	
<u>Figure</u>		Page
2-1	PEAK PRESSURE AS A FUNCTION OF RANGE FROM 1/2-SCALE WELLHEAD SEVERANCE EXPLOSION	2 - 4
2-2	IMPULSE AS A FUNCTION OF RANGE FROM 1/2-SCALE WELLHEAD SEVERANCE EXPLOSION	2-5
2-3	ENERGY FLUX DENSITY AS A FUNCTION OF RANGE FROM 1/2-SCALE WELLHEAD SEVERANCE EXPLOSION	2-6
2-4	PMAX - COMPARISON OF EQUATION FOR 56-LB SEVERANCE EXPLOSION WITH 10-LB FREE-WATER EXPLOSION	2-9
2-5	DECAY CONSTANT - COMPARISION OF EQUATION FOR 56-LB SEVERANCE EXPLOSION WITH 10-LB FREE-WATER EXPLOSION	2-10
2-6	PMAX·T - COMPARISON OF EQUATION FOR 56-LB SEVERANCE EXPLOSION WITH 10-LB FREE-WATER EXPLOSION	2-11
3-1	10%, 50% & 90% KILL PROBABILITY CONTOURS FOR WELLHEAD SEVERANCE EXPLOSION - 200-FT WATER DEPTH	. 3-2
3-2	10% KILL PROBABILITY CONTOURS FOR WELLHEAD SEVERANCE EXPLOSION - 500-FT WATER DEPTH	3-3
3-3	10% KILL PROBABILITY CONTOURS FOR WELLHEAD SEVERANCE EXPLOSION - 1000-FT WATER DEPTH	3-4
	TABLES	
<u>Table</u>		Page
2-1	PRESSURE MEASUREMENTS FROM 1/2-SCALE WELLHEAD SEVERANCE TEST	2-3

	۸
en e	
	•
	•

INTRODUCTION

Most countries require that abandoned oil well components be removed from the seabed. Typically, wellheads are severed 15 to 20 feet below the ocean bottom and the freed portions are lifted to the surface for salvage. An explosive charge detonated inside the wellhead casing at the desired severance point is an efficient and popular way of cutting the casing. A major problem with this method is the potential of the severance explosion for killing fish and marine life.

In response to this problem the Naval Surface Weapons Center (NSWC) has recently completed a series of explosion tests to determine the amount of explosive necessary for severance and the resultant pressure field in the water¹. These tests were done using simulated model wellheads on 1/2 scale. Using these pressure measurements as input for full-scale-explosion computations, this report presents an analysis of the potential of wellhead severance explosions for inflicting unwanted fish-kill. This analysis is restricted to swim bladder fish and is based on the method developed by Goertner². The fish-kill data base used consists of data reported by Goertner² and Yelverton et al³ plus additional unpublished data of NSWC and the Chesapeake Biological Laboratory.

¹Faux, W. H., "A Cursory Look at the Environmental Effect of the Severing of Oil Wellheads," Transactions of the 1981 Explosives Conference June 9-11, 1981, Houston, TX, Sponsored by the Drilling Technology Committee of the International Association of Drilling Contractors.

²Goertner, J. F., "Dynamical Model for Explosion Injury to Fish," NSWC/WOL TR 76-155, 1978.

³Yelverton, J. T., et al, "The Relationship Between Fish Size and their Response to Underwater Blast," Lovelace Foundation, DNA Report 3677T, 1975.

The method consists of an approximate calculation for the extreme values of compression and extension of the fishes' gas-filled swim bladder in response to the explosion pressure wave. The calculations are made for the damped radial oscillations of a spherical air bubble in water. The kill probability is then calculated as an experimentally determined function of the ratio of maximum to minimum radius during the oscillatory response.

CHAPTER 2 CALCULATION INPUTS

PRESSURE-TIME INPUT. Three 1/2-scale severance explosions were fired at 7.5-ft depth in a mud bottom under 26 feet of water. Cylindrical charges made from three different explosives--Comp C-4, TNT, and nitromethane--were used to cut the simulated wellhead casings, which were made from steel pipe, with inside diameters of 15, 8 and 5 inches. The annuli between the casings were filled with cement. Total weight of each charge--including pentolite boosters used for the TNT and nitromethane--was approximately 7 pounds. All three charges severed the casings satisfactorily. The Comp C-4 explosion gave significantly higher shock wave peak pressure, impulse and energy flux density in the overlying water. Since we desired a realistic "worst case" for this analysis we selected the underwater shock wave measurements from the Comp C-4 test as input data for this study.

For the purpose of this study it would be irrelevant to characterize the underwater pressure signatures from these severance explosions in all their intricate details. The principal result of the confinement, added mass and attenuation caused by the casing and surrounding bottom material is a considerably lower peak pressure and an increase in the duration of the principal pulse from these explosions. Heathcote¹ reports measured values for the underwater peak pressure, impulse and energy flux density at 22 pressure gage locations on the three underbottom explosion tests. The shockwave impulse, $I = \int p(t) dt$, and the

¹See footnote 1 on page 1-1

energy flux density, $E = \frac{1}{\rho_0 c_0} \int [p(t)]^2 dt$, were numerically integrated to 1 millisecond duration. These data together with gage locations relative to the severance charge are reproduced in Table 2-1 for the Comp C-4 explosion. The data are plotted as a function of radial distance from the charge in Figures 2-1 through 2-3. These data are the input pressure data for this study.

In Figures 2-1 through 2-3 separate symbols are used to distinguish between gage locations having different values of polar angle, θ , relative to the vertical direction. Note that all three plots show a simple power law dependence of the dependent variable with range, R, indicated by the straight lines. On the impulse and energy flux density plots these lines were drawn through the data points for polar angle, $\theta \le 30^{\circ}$. On these plots inclusion of the additional data having θ -values in the range, $30^{\circ} < \theta \le 60^{\circ}$, does not appear to change the power law dependence on R. However, it does appear to increase the data scatter (random error).

On the peak pressure plot the line shown is an eye fit to the data, suitable for extrapolation to greater range from the charge. On this plot the data points for θ -values in the range, $30^{\circ} < \theta \le 60^{\circ}$, indicate the higher pressures were measured at these gages.

For use in the computations of this study, the solid lines drawn through the PMAX, I and E data shown in Figures 2-1 through 2-3 were expressed as under-water shockwave similitude equations⁴

$$PMAX = 8510 \left(\frac{R}{W^{1/3}}\right)^{-1.18}$$
 (2-1)

$$I = 0.931 \text{ W}^{1/3} \left(\frac{R}{W^{1/3}}\right)^{-1.11} \tag{2-2}$$

$$E = 622 W^{1/3} \left(\frac{R}{W^{1/3}}\right)^{-2.23}$$
 (2-3)

2-2


Cole, Robert H., "Underwater Explosions," Princeton University Press, 1948, p. 239.

TABLE 2-1 PRESSURE MEASUREMENTS FROM 1/2-SCALE WELLHEAD SEVERANCE TEST

Charge: 7.0 1b Comp C-4


Gage Position	Range (ft)	Polar Angle (deg)	PMAX (psi)	I (lb-sec/in²)*	E (in-lb/in ²)*
1	9.6	25	1182	0.287	32
2	10.4	23	1017	0.282	28
3	12.0	20	830	0.220	18
4	12.9	18	929	0.218	17.5
- 5	16.75	. 14	641	0.153	9.3
1 2 3 4 5 6 7 8 9	17.6	14	581	0.149	8.1
7	22.1	11	447	0.121	5.0
8	26.0	9	365	0.099	3.55
9	27.0	9	351	0.096	3.3
10	12.6	46	1386	0.218	19.6
11	13.3	43	1146	0.184	14.8
12	14.6	38	975	0.181	13.4
13	13.4	42	829	0.181	12.7
14	18.8	29	552	0.145	7.4
15	19.6	27	575	0.151	7.2
16	27.8	19	375	0.092	. 3.1
17	16.75	57	690	0.141	7.3
18	17.25	54	749	0.141	7.5
19	18.6	49	703	0.124	6.6
20	22.0	39	560	0.111	5.1
21	21.2	11	478	0.124	5.5
22	23.8	22	480	0.107	4.3

^{*}Integrated to 1.0 milliseconds




CHARGE: 7.0 LB COMP C-4

FIGURE 2-1 PEAK PRESSURE AS A FUNCTION OF RANGE FROM ½-SCALE WELLHEAD SEVERANCE EXPLOSION



CHARGE: 7.0 LB COMP C-4

FIGURE 2-2 IMPULSE AS A FUNCTION OF RANGE FROM ½-SCALE WELLHEAD SEVERANCE EXPLOSION



CHARGE 7 0 LB COMP C-4

FIGURE 2-3 ENERGY FLUX DENSITY AS A FUNCTION OF RANGE FROM ½-SCALE WELLHEAD SEVERANCE EXPLOSION

where R is the radial distance from the charge in feet, W is the explosive weight in pounds, PMAX is the peak pressure in psi, I is the impulse in $lb-sec/in^2$, and E is the energy flux density in $in-lb/in^2$.

Exponential Pulse Approximation. To facilitate the computations using the dynamical model developed by Goernter² we approximated the principal pulse from the wellhead severance explosion by an exponential pulse having peak pressure, PMAX, given by Equation 2-1 and impulse, $I = \int_{0}^{\infty} PMAX \cdot EXP(-t/\tau) \cdot dt$, given by Equation 2-2 where τ is the decay constant of the exponential pulse. Since $\int_{0}^{\infty} PMAX \cdot EXP(-t/\tau) \cdot dt = PMAX \cdot \tau$, using Equations 2-1 and 2-2 we can express τ as

$$\tau = 109 \times 10^{-6} \text{ W}^{1/3} \left(\frac{\text{R}}{\text{W}^{1/3}}\right)^{0.07}$$
 (2-4)

where τ is the decay constant in seconds.

EQUIVALENT FREE-WATER EXPLOSION. Due to the short time available for this study we used existing computer programs which were designed for explosions of bare charges in free water for the computations in this report. This necessitated determining the charge weight for a free-water explosion which was in some sense equivalent to a 56-lb Comp C-4 severance explosion buried 15 feet in a mud bottom. Previous discussion with the sponsor, the U.S. Geological Survey, had set the range of full-scale water depths of interest in wellhead severance explosions at 200 to 1000 feet. With these water depths and 15-ft charge burial depth, preliminary computations indicated that the significant fish-kill would occur between ranges of 15 and 1500 feet from the charge. Thus, to make the kill probability predictions for this report, we selected an explosive weight of bare pentolite in free water which roughly optimized the correspondence between pressures signatures - over this range - for the severance explosion (Equations 2-1 through 2-4) and a bare

²See footnote 2 on page 1-1.

pentolite charge in free water.* The equivalent weight of explosive selected was 10 pound pentolite, which gives peak pressures, PMAX, over the 15 to 1500 ft range somewhat too high, values for decay constant, τ , somewhat too low, and values in the product, PMAX· τ -- proportional to the impulse -- which are about as good as we can get by this method (Figures 2-4 through 2-6).

^{*}Price, R. S., Naval Surface Weapons Center, private communication, 1981.




FIGURE ?-4 P_{MAX} — COMPARISON OF EQUATION FOR 56-LB SEVERANCE EXPLOSION WITH 10-LB FREE-WATER EXPLOSION




FIGURE 2-5 DECAY CONSTANT — COMPARISON OF EQUATION FOR 56-LB SEVERANCE EXPLOSION WITH 10-LB FREE-WATER EXPLOSION




FIGURE 2-6 $P_{\mbox{\scriptsize MAX}}$ • $_{\mbox{\scriptsize T}}$ – COMPARISON OF EQUATION FOR 56-LB SEVERANCE EXPLOSION WITH 10-LB FREE-WATER EXPLOSION

KILL PROBABILITY CONTOURS

Figures 3-1 through 3-3 show the results of this study. The pressure field as modified by surface reflection and bulk cavitation was calculated for free-water charge depths of 215, 515 and 1015 feet, respectively, using a 10 pound equivalent weight free-water pentolite explosion. (Figure 3.1.1 of Reference 2 shows the form of a typical pressure signature.) Then for each two-dimensional array of pressure field values, the swim bladder response and corresponding kill probability were calculated for three different sizes of fish. Finally, contours for predicted kill probabilities of 90%, 50% and 10% were interpolated through the two-dimensional arrays of computed kill probabilities (Figures 3-1 through 3-3).

²See footnote 2 on page 1-1




FIGURE 3-1 10%, 50% & 90% KILL PROBABILITY CONTOURS FOR WELLHEAD SEVERANCE EXPLOSION — 200-FT WATER DEPTH




FIGURE 3-2 10% KILL PROBABILITY CONTOURS FOR WELLHEAD SEVERANCE EXPLOSION — 500-FT WATER DEPTH




FIGURE 3-3 10% KILL PROBABILITY CONTOURS FOR WELL HEAD SEVERANCE EXPLOSION — 1000-FT WATER DEPTH

CONCLUSIONS

- 1. For wellhead severance explosions in water depth of 200 feet, significant fish kills can occur near the surface out to a horizontal range of about 900 feet for small fish (1-oz weight). Larger fish near the surface are considerably less vulnerable to explosion injury. One-pound fish near the surface can be killed out to a range of about 300 feet. Near the bottom significant kills of all sizes of fish are limited to a maximum horizontal range of about 70 feet.
- 2. In water depth of 500 feet, the hazard to all fish is considerably reduced and is probably significant only for small fish. One-ounce fish near the surface can be killed out to a horizontal range of about 700 feet. The only other fish which are vulnerable to injury are those near the bottom in the immediate vicinity of the wellhead -- within a radius of 30 to 40 feet from the charge.
- 3. For severance explosions in water of 1000-ft depth, no significant kills of swim bladder fish will occur.

					,
		•			
			•		
,					
•					
		•		,	
•					
	•,				
			•		
			,		
			•		
•	•	$x^{(i)} = x^{(i)}$			
			÷		
					*
					•
	**				
	•				
		•			
		•			
			•		
	•				
	•				
•					

DISCUSSION

These results should be considered preliminary and are limited to swim bladder fish. Although these results are based on the close-in pressure field for a 56-lb Comp C-4 severance explosion, they can (and should) be applied to severance explosions using different explosives and charge weights. The uncertainties inherent to the problem of predicting fish-kill are greater than the variations in explosive output among common explosives. And, since the explosive weights for most wellhead severance explosions will -- from practical considerations -- be within a factor of two of the 56-lbs Comp C-4 used for this study, we have not stated the explosive weight on the graphs showing computed fish-kill probability contours (Figures 3-1 through 3-3). In other words, the author believes the results of this report to be valid for wellhead severance explosions in the range, $28 \text{ lb} \leq W \leq 112 \text{ lb}$, where W is the explosive charge weight.

Possible steps for improving these predictions would include:

- Computation of the pressure field -- as modified by surface reflection and bulk cavitation -- based on the fits to the 1/2-scale severance test data (Equations 2-1 and 2-4).
- Bulk cavitation computations by the method of Gaspin and Price⁵ to compare the predicted cavitation regions resulting from the fits to the 1/2-scale severance test data with those obtained by using the free-water pentolite similitude equations

⁵Gaspin, J. B., and Price, R. S., "The Underpressure Field from Explosions in Water as Modified by Cavitation," NOL Technical Report NOLTR 72-103, 1972.

- Detailed comparison of predictions based on the dynamical model with predictions based on other damage variables, such as energy and impulse.

It should also be stressed that the actual kill at any site depends on the fish population and its distribution in the water column.

DISTRIBUTION

•	1.0				copies
U.S. Geological Survey Ventura District 145 North Brent Street, Suite 102					
Ventura, California 93003					1
U.S. Geological Survey					
Freeport District 200 West 2nd Street, Suite 300 Freeport, Texas 77541					
,					1
U.S. Geological Survey Houma District					
1700 Grand Caillou P.O. Box 1269					
Houma, Louisiana 70360					1
U.S. Geological Survey					
Lafayette District 224 Bendel Road					
P.O. Box 52289 Lafayette, Louisiana 70501				•	
					. 1
U.S. Geological Survey Lake Charles District					
3727 Ryan Street P.O. Box 6088					
Lake Charles, Louisiana 70601					1
U.S. Geological Survey					
Metairie District 137 Imperial Office Building					
3301 North Causeway Boulevard P.O. Box 7966					
Metairie, Louisiana 70010		• .	•		1
U.S. Geological Survey					
Atlantic Area 1725 K Street, Suite 204			• • • • • • • • • • • • • • • • • • •		
Washington, D.C. 20006		•	• Program de la disconsidera de la companya del companya del companya de la compa		1
J.S. Geological Survey					
North Atlantic District Mary Dunn Road, East Ramp 8506					
Barnstable Municipal Airport Hyannis, Massachusetts 02601					1

•		•		Copies
U.S. Geological Survey Research and Development Program 620 National Center, Conservation Div 12201 Sunrise Valley Drive Reston, Virginia 22092	vision			30
U.S. Geological Survey Eastern Region/Atlantic OCS Region 1725 K Street, N.W., Suite 204 Washington, D.C. 20006				2
U.S. Geological Survey Alaska Region/Alaska OCS Region P.O. Box 259 Anchorage, Alaska 99510				2
U.S. Geological Survey Pacific OCS Region 1340 West 6th Street Los Angeles, California 90017				2
U.S. Geological Survey Gulf of Mexico OCS Region Imperial Office Building P.O. Box 7944 Metairie, Louisiana 70010				2
U.S. Geological Survey Chief, Conservation Division 610 National Center 12201 Sunrise Valley Drive Reston, Virginia 22092				1
U.S. Geological Survey Deputy Division Chief, Offshore Minerals Regulation 640 National Center, Conservation Di 12201 Sunrise Valley Drive Reston, Virginia 22092	vision			1
U.S. Geological Survey Mid Atlantic District 26 South Pennsylvania Avenue Atlantic City. New Jersey 08401				1

	copies
Commander Naval Sea Systems Command Attn: SEA-322 (J. Sullivan) SEA-322 (D. M. Hurt) SEA-322 (R. E. Fuss) SEA-62R32 (G. D. Edwards) SEA-62R (W. W. Blaine) SEA-09G32 SEA-03B	1 1 1 1 1 2
Washington, D.C. 20362	1
Commander David Taylor Naval Research & Development Center Attn: Code 17 Code 1740 Code 1740.1 Code 1750 Code 1720 Code 1720 Code 1720.3 Code 042 Bethesda, Maryland 20084	1 1 1 1 1 1
Underwater Explosions Research Division David Taylor Naval Ship Research & Development Center Attn: Technical Reference Center R. Oliver Portsmouth, Virginia 23709	1
Director Naval Research Laboratory Attn: Code 2027 Code 8400 Code 8406 Washington, D.C. 20375	1 1 1
Commanding Officer Naval Underwater Systems Center Attn: Technical Library Newport, Rhode Island 02840	1
Defense Technical Information Center Cameron Station Nexandria, Virginia 22314	12

	•	Copies
Office of Naval Research Attn: Code 480 800 N. Qunicy Street Arlington, Virginia 22217		1
Library of Congress Attn: Gift and Exchange Division Washington, D.C. 20540		4
Commander Naval Coastal Systems Center Attn: Code 734 (H. Loftin) Library Panama City, Florida 32407		1 1
Chief of Naval Material Office of Naval Technology Attn: MAT-07 (J. W. Enig) Washington, D.C. 20360		1
Director Waterways Experiment Station Attn: Technical Library J. N. Strange Kim Davis P.O. Box 631 Vicksburg, Mississippi 39180		1 1 1
Naval Biosciences Laboratory Naval Supply Center Oak Attn: Louis H. DiSalvo LTJG John F. Wyman Oakland, California 94625		1
Commanding Officer Naval Underwater Systems Center Attn: Code EA 11 (Roy R. Manstan) Newport, Rhode Island 02840		1
Commander Naval Ocean Systems Center Attn: G. B. Anderson Code 406 (S. Yamamoto) D. A. Wilson Code 40 (F. G. Wood) Code 6565 Michael H. Salazar San Diego, California 92152		1 1 1 1 1

Comment	Copies
Commander Naval Ocean Systems Center Attn: Jack W. Hoyt	1 1 1
Naval Ocean Systems Center Hawaii Laboratory Attn: Evan C. Evans, III Head Marine Environmental Management Office P.O. Box 997, Kailua, Oahu Hawaii, 96734	1 1
Officer in Charge New London Laboratory Naval Underwater Systems Center Attn: Albert B. Brooks Code TA13 (Charles L. Brown, Jr.) New London, Connecticut 06329	1 1
Commanding Officer Naval Explosive Ordnance Disposal Facility Attn: Library Division Code 5D, (Lionel A. Dickinson) Richard Burdette Lyle Malotky Indian Head, Maryland 20640	1 1 1
Commanding Officer Naval Explosive Ordnance Disposal School Attn: LCDR E. W. McConnell Indian Head, Maryland 20640	1
Officer in Charge Civil Engineering Laboratory Naval Construction Battalion Center Attn: Code L70 Code L71 Code L43 Code L65 Port Hueneme, California 93043	1 1 1 1

	<u>Copies</u>
Commanding Officer Naval Air Station Attn: A. L. Clark, Environmental Protection Coordinator Public Works Department Patuxent River, Maryland 20670	1
U.S. Army Engineer District 100 McAllister Street Attn: Tom Crews, III, Environmental Branch San Francisco, California 94102	1
U.S. Army Engineer Division, Pacific Ocean Environmental Section Attn: Michael T. Lee, Biologist Bldg. 230, Ft. Shafter APO San Francisco 96558	1
ADTC/DLV Attn: J. C. Cornette Eglin AFB, Florida 32542	1
National Marine Fisheries Service Auke Bay Biological Laboratory Attn: Theodore Merrell P.O. Box 155 Auke Bay, Alaska 99821	1
National Marine Fisheries Service Water Resources Division Attn: Dale R. Evans, Chief P.O. Box 1668 Juneau, Alaska 99802	1
National Marine Fisheries Service Southwest Fisheries Center P.O. Box 271 La Jolla, California 92037	1
Department of Commerce Biological Laboratory Midford, Connecticut 06460	1
Department of the Interior Attn: Karen Bachman Mark L. Holmes 1107 NE 45th Street Suite 110 Seattle, Washington 98105	1

		Copies
Department of the Interior Bureau of Sports Fisheries and wildlife Interior Building Attn: John S. Gottschalk, Director Washington, D.C. 20240	-	1
Bureau of Commerical Fisheries Interior Building Attn: Philip M. Rordel, Dir stor Washington, D.C. 20240		1
State of Maryland Fish and Wildlife Administration Attn: Charles Frisbie Barbara Holden Howard J. King Annapolis, Maryland 21404		1 1 1
State of North Carolina Department of Natural and Economic Resources Division of Marine Fisheries Attn: Willard Lane, Artificial Reef Program Jim Tyler, Artificial Reef Program Box 769 Morehead City, North Carolina 28557		1 1
South Carolina Marine Resources Division Attn: Michael D. McKenzie 2024 Maybank Highway Charleston, South Carolina 29412		1
Trust Territory Environmental Protection Board Attn: M. Falanruw, Staff Ecologist P.O. Box 215 Yap, W.C.I. 96943		1
State of Alaska Department of Fish and Game Attn: Lance L. Trasky, Fisheries Research Biologis: B33 Raspberry Road Anchorage, Alaska 99502		1
eputy Commissioner laska Department of Fish and Game upport Building ttn: Joseph R. Blum		1

	Copies
State of Alaska Department of Fish and Game Habitat Section 333 Raspberry Road Anchorage, Alaska 99501	1
Department of Fish and Game Wildlife Protection Branch 1416 Ninth Street Sacramento, California 95814	1
State of California Marine Resources Division Attn: Doyle Gates, Regional Manager 350 Golden Shore Long Beach, California 90802	1
State of Florida Department of Natural Resources Larson Building Tallahassee, Florida 32304	1
State of Louisiana Wildlife and Fisheries Commission Attn: Fred Dunham P.O. Box 44095, Capital Station Baton Rough, Louisana 70804	1
Virginia Institue of Marine Science Attn: William J. Hargis, Director Gloucester Point, Virginia 23062	1
Director Woods Hole Oceanographic Institution Attn: Earl E. Hays Lincoln Baxter, II Library Woods Hole, Massachusetts 02543	1 1 1
Director Scripps Institution of Oceanography Attn: Fred Spiess La Jolla, California 92037	1 ,

•	•	<u>Copies</u>
School of Oceanography Oregon State University Attn: A. G. Carey, Jr. Librarian Corvallis, Oregon 97331		1
Chesapeake Bay Institute The Johns Hopkins University Baltimore, Maryland 21218		1
Chesapeake Biological Laboratory Attn: T. S. Y. Koo Joseph A. Mihursky Martin L. Wiley John S. Wilson P. O. Box 38 Solomons, Maryland 20688		1 1 1 1
Marine Physical Laboratory, S10/UCSD Attn: Charles B. Bishop Bldg. 106, Naval Undersea Center San Diego, California 92106		1
University of Hawaii at Manoa Hawaii Institute of Marine Biology Attn: George H. Balazs, Jr., Marine Biologist P.O. Box 1346, Coconut Island Kaneohe, Hawaii 96744		1
Department of Biology Duniata College Attn: Robert L. Fisher Huntingdon, Pennsylvania 16652		1
Marine Resources Division Malifornia State Fisheries Lab Mattn: Robert Kanlen Magnolia Magnolia Magnolia Magnolia		1
obert E. Eckels & Associates onsulting Engineers 102 Youngfield olden, Colorado 80401		1

	Copies
Woodward Clyde Consultant Attn: Jack Kiker Box 1149 Orange, California 92668	· 1·
B.O.C. Sub Ocean Services Attn: Thomas L. Kirchberg 1022 Wirt Road Houston, Texas 77055	1
Lovelace Biomedical & Environmental Research Institute, Inc. Attn: Donald R. Richmond E. Royce Fletcher Robert K. Jones John T. Yelverton P. O. Box 5890 Albuquerque, New Mexico 87115	1 1 1
Tetra Tech, Inc. Attn: Li-San Hwang 630 N. Rosemead Blvd. Pasadena, California 91107	1
Explo Precision Engineering Corporation Attn: John J. Ridgeway Manager of Technical Services Gretna, Louisana 70053	1

1								
•					·			
•								
					•			
		•						Y
						•		
	•							
				. ,				
							. •	
		•						
							•	
	·· .							
								•
					•			
			~	•	·			
•								
						•		
		•						

